

RECEIVED
CENTRAL FAX CENTER

NOV 30 2005

AMENDMENTS TO THE CLAIMS

For the Examiner's convenience, all pending Claims are set forth below and have been amended where noted:

1. (Currently Amended) A self energizing tube connector for engaging a pressurizable part comprising:
 - a. a tube capable of sustaining pressures up to 50,000 psi without deforming comprising an upstream tube end and a downstream tube end;
 - b. a ferrule assembly comprising:
 - i. a front ferrule;
 - ii. a rear ferrule;
 - iii. a lifting component, wherein the lifting component is a ring comprising an upstream edge and a downstream edge, wherein the upstream edge has a diameter larger than the downstream edge and wherein the lifting component slidingly engages the front ferrule to cause an upstream seal to form between the pressurizable part and the front ferrule tube; and
 - iv. a downstream seal between the front ferrule and the tube;
 - c. a coupling nut for sliding over the tube and disposed downstream of the rear ferrule for engaging the pressurizable part, wherein the coupling nut is adapted to tighten against the rear ferrule to tighten the front ferrule and lifting mechanism, wherein the coupling nut ~~[[which]]~~ compresses the front ferrule against the pressurizable part and the tube.
2. (Previously Amended) The tube connector of claim 1, wherein the tube comprises an outer diameter ranging between about 1/16 inches to about 12 inches.
3. (Original) The tube connector of claim 2, wherein the tube comprises an outer

diameter ranging between about 1/8 inches to about 1 inch diameter.

4. (Original) The tube connector of claim 1, wherein the front ferrule, the rear ferrule, and the lifting component comprise a deformable material that deforms upon compression with the coupling nut.
5. (Original) The tube connector of claim 4, wherein the deformable material is a metal or plastic.
6. (Original) The tube connector of claim 1, wherein the tube is a metal tube or a plastic tube.
7. (Currently Amended) The tube connector of claim 1, wherein a pressure in the tube ranges between 1 atm to 25,000 psi.
8. (Original) The tube connector of claim 1, wherein the coupling nut comprises a threaded engagement with the pressurizable part.
9. (Previously Amended) The tube connector of claim 1, wherein the pressurizable part is a down hole safety valve, a plurality of chemical injection assemblies, a plurality of tubing hangers, a plurality of blow out preventors, a plurality of subsea Christmas trees, or a plurality of packers.
10. (Cancelled)
11. (Cancelled)
12. (Original) The tube connector of claim 1, wherein the front ferrule comprises a conical shape for engaging the pressurizable part.
13. (Original) The tube connector of claim 1, wherein the coupling nut is a jam nut.
14. (Cancelled)
15. (Cancelled)
16. (New) A self energizing tube connector for engaging a pressurizable part

comprising:

- a. a tube capable of sustaining pressures up to 50,000 psi without deforming comprising an upstream tube end and a downstream tube end;
- b. a ferrule assembly comprising:
 - i. a front ferrule;
 - ii. a rear ferrule;
 - iii. a lifting component, wherein the lifting component further comprises a groove disposed adjacent the upstream edge to prevent sealing at the upstream edge of the lifting component and, wherein the lifting component slidably engages the front ferrule to cause an upstream seal to form between the pressurizable part and the tube; and
 - iv. a downstream seal between the front ferrule and the tube;
- c. a coupling nut for sliding over the tube and disposed downstream of the rear ferrule for engaging the pressurizable part, wherein the coupling nut is adapted to tighten against the rear ferrule to tighten the front ferrule and lifting mechanism, wherein the coupling nut compresses the front ferrule against the pressurizable part and the tube.

Applicant believes that no new matter has been added with these amendments.